

**SHENZHEN ABT ELECTRONICS CO., LTD.**

Tel:86-755-89958277 Fax:86-755-89958274 Email:sales@SZABT.com Http://www.SZABT.com

SPECIFICATION		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :	1/22/2006 8:21:00 PM			
COMMON/UNITE	DOC. NO:		REV.: 1.0	PAGE: 1 OF 1

3PX0-A7030 Smart 3-Stages SLA Battery charger				
	ITEM	UNIT	SPECIFICATION	REMARK
<b>INPUT</b>				
01	Rating Input Voltage	V ac	100~240Vac 50/60Hz	
02	Input voltage range	V ac	90~264Vac	
03	Rating Input Current	A	1.1Arms	INPUT:220V OUTPUT:Full load
04	Max. input power	W	80	
<b>OUTPUT</b>				
05	Rating output voltage	V dc	28V	
06	Output voltage range	V dc	20VDC ~ 30VDC	
07	Suit with Battery type		24V 8~12Ah VRLA	
08	Charging current ( stage 1)	A	1.85± 0.15@26V	
09	Charging voltage (stage 2)	V	29.4V +-0.2V	
	Floating voltage (stage 3)	V	27.8V+-0.2V	
10	Cut-off current(stage 2→3)	A	<0.41+-0.04A	
11	Typical charging time	hour	8	
12	Max. output power	W	60W	
13	Hold-on time	ms	NC	Input: 220Vac Output: Full load
14	Ripple current	mA	100	Input: 220Vac Output: Full load
15	Charge finish condition		V>29V + I<0.4A	
16	LED color		Red: charging Green: finish/idle	
17	Output protect	-	OCP & OVP	
18	Efficiency	%	80%	At max. load
<b>Environment</b>				
19	Operate temperature	°C	-10 ~ +40	Full load & natural convection.
20	Operate humidity	%RH	< +90	Relative humidity, non-condensing.
21	Storage temperature	°C	-40 ~ +70	
22	Storage humidity	%RH	0 ~ +95	Relative humidity, non-condensing.
23	Cooling	-	Natural convection	
24	Temperature factor	%	--	
25	Vibration resistance		5MM/50HZ/600S	Non-operating condition.
26	Impact resistance		1 meter drop test >= 3 times	Non-operating condition.
<b>Mechanical</b>				
27	Weight	g	550	
28	Size	mm	129X91X68	Casing only
29	Connectors	-	Defined when order	
<b>Safety</b>				
30	Max. temperature rise	°C	< 40 on casing	At any line and Max. Load
31	Safety standards	-	IEC335-2-29	
32	EMC standard	-	EN55014	
33	MTBF	hrs	30000	
34	Limited power source	VA	-	
35	ESD	kV	8.0	
36	Hi-Pot Insulation	V	i/p to o/p: 3000 (1 min.)	For final unit, cut-off current =10mA