

**SHENZHEN ABT ELECTRONICS CO., LTD.**

Tel:86-755-89958277 Fax:86-755-89958274 Email:sales@SZABT.com Http://www.SZABT.com

<b>SPECIFICATION</b>		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :	10/21/2008 10:26:00 AM			
COMMON/UNITE	DOC. NO:	REV.: 2	PAGE: 1 OF 1	

**3P10-N0508 SMART NIMH BATTERY CHARGER**

NO	ITEM	UNIT	SPECIFICATION	REMARK
<b>INPUT</b>				
01	RATING INPUT	V ac	100~240Vac 50/60Hz	
02	INPUT RANGE	V ac	90~264Vac	
03	RATING INPUT CURRENT	A	0.1Arms	INPUT:120V OUTPUT:Full load
04	MAX. INPUT POWER	W	6	
<b>OUTPUT</b>				
05	RATING OUTPUT VOLTAGE	V dc	6.4V	
06	OUTPUT VOLTAGE RANGE	V dc	4VDC ~ 8VDC	8V is open-circuit voltage
07	SUIT WITH BATTERY	Ah	3.6~4.8V 700~4000mAh NIMN/NICD	
08	CHARGE CURRENT	A	0.6A~0.8A	
09	TRICKLE CURRENT	A	<0.08	
11	INNER TIMMER(typical)	hour	8	From 1~10 hours, defined by user
12	MAX. OUTPUT POWER	W	4W	
13	HOLD-ON TIME	ms	NC	Input: 120Vac Output: Full load
14	RIPPLE CURRENT	mA	30	Input: 120Vac Output: Full load
15	MAIN CHARGE END CONDITION		- $\Delta V > 5mV$ /CELL(typical) or $V_{MAX} \geq 1.6V$ /cell(typical) or Timer out.	For NiCd battery, $V_{max}$ is 1.8V/cell This value can be defined by user.
16	LED INDICATION		RED: MAIN CHARGE GREEN: FINISHED	
17	Output shorted Protection Output reverse Protection	-	YES No	
18	EFFICIENCY	%	60%	At max. load
<b>ENVIRONMENT</b>				
19	OPERATE TEMP.	°C	-10 ~ +40	Full load & natural convection.
20	OPERATE HUMIDITY	%RH	< +90	Relative humidity, non-condensing.
21	STORAGE TEMP.	°C	-40 ~ +70	
22	STORAGE HUMIDITY	%RH	0 ~ +95	Relative humidity, non-condensing.
23	COOLING	-	Natural convection	
24	TEMP. FACT	%	--	
25	VIBRATION		5MM/50HZ/600S	Non-operating condition.
26	IMPACT		1 meter drop test $\geq 3$ times	Non-operating condition.
<b>MECHANICAL</b>				
27	WEIGHT	g	120	
28	SIZE	mm	81X51X28	Casing only
29	Input/Output Cord and Connecters.	-	Defined by user	
<b>SAFETY</b>				
30	TEMP. RISE	°C	< 40 on casing	At any line and Max. Load
31	SAFETY STANDARD	-	EN60950 UL1950	
32	EMC	-	EN55022 B	
33	MTBF	hrs	30000	
34	ESD	kV	8.0	
35	HI-POT	V	i/p to o/p: 3000 (1 min.)	For final unit, cut-off current =10mA